

3 способа достать текст из группы radiobutton

```
package rf;

import java.util.ArrayList;
import java.util.Arrays;
import java.util.List;
import java.util.Optional;
import javax.swing.JRadioButton;

public class RadioFrame extends javax.swing.JFrame {
    List<JRadioButton> buttons;

    public RadioFrame() {
        initComponents();
        buttons = new ArrayList<>(Arrays.asList(jRadioButton1, jRadioButton2,
jRadioButton3, jRadioButton4));
    }

    private void jButton1ActionPerformed(java.awt.event.ActionEvent evt) {
        String s = "Not selected";
        for (JRadioButton button : buttons) {
            if (button.isSelected()) {
                s = button.getText();
                break;
            }
        }
        jButton1.setText(s);
    }

    private void jButton2ActionPerformed(java.awt.event.ActionEvent evt) {
        Optional<JRadioButton> btn =
buttons.stream().filter(JRadioButton::isSelected).findAny();
        //isPresent - есть в наличии
        if (btn.isPresent()) {
            jButton2.setText(btn.get().getText());
        }
    }

    private void jButton3ActionPerformed(java.awt.event.ActionEvent evt) {
        // нужен потребитель
        buttons.stream().filter(JRadioButton::isSelected).findAny().ifPresent(btn->
jButton3.setText(btn.getText()));
    }
}
```